

Cetronic Power Solutions Ltd

Unit 5, Optima Business Park, Pindar Road, Hoddesdon, Herts. EN11 0DY, United Kingdom

Tel: +44 (0)1920 871077 Fax: +44 (0)1920 871337

E-mail: sales@cetronicpower.com



Certificate No. 13590

Thermostats

Model Type 25/75 Automatic Reset

Electrical Rating						
10A 250 VAC Resistive load						
12A 125VAC Resistive load						
5A 250VAC Inductive load						
6A 125VAC Inductive load						
Contact Resistance						
Silver Contact ≤ 50 mΩ						
Gold Contact ≤ 10 mΩ						
Insulation Resistance						
≥ 10 GΩ						
Dielectric Strength						
Contact and case 50 Hz ≤ 3000V eff.						
Open contact 50 Hz ≥ 1000V eff.						
Heating Resistance						
180ºC						
Switching Durability						
100000 times at rated load						



Туре	25	75
Set T ^o C	±3ºC	±5ºC
Reset TºC	±5ºC	N/A

	Model	Model Contact	Mounting	Terminal	Temperature in ^o C	
					Set T ^o C	Reset TºC
Example	25	2	98	01	100	085
	25	2	00	01	From	± 5ºC minimum
		(Opening, Silver)	(Without Mounting)	(Quick)	0 - 150°C ± 3°C	
		4	92	02		±10/15ºC
		(Opening, Gold Plated)	(Moveable Bracket)	(Quick)		(Standard)
		0	97	04		999 (Uncontrolled)
		(Closing, Silver)	(Moveable Bracket)	(Quick)		,
		5	98	11		
		(Closing, Gold Plated)	(Moveable Bracket)	(Quick)		
			94	12		
			(Fixed Bracket)	(Quick)		
			96	14		
			(Fixed Bracket)	(Quick)		
			85	21		
			(Threaded Stud)	(Solder Tags)		
			86	22		
			(Threaded Stud)	(Solder Tags)		
			87	23		
			(Threaded Stud)	(Solder Tags)		
			88	24		
			(Threaded Stud)	(Solder Tags)		
			77	41		
			(Watertight)	(Wire)		
			78			
			(Watertight)			
			68			
			(Watertight)			